



Scrape, grade and level almost any playing field.

A good rear blade is like a trusty pocketknife. You never run out of uses for it. Whether you're landscaping the yard, grading driveways or field roads, cleaning up a construction site, plowing snow or even cleaning livestock pens, you can always count on the strength and durability of these blades. Quickly and easily adjust the tilt, angle and offset to make short work of any job.

INNOVATIVE DESIGN AND TECHNOLOGY



ASABE QUICK HITCH COMPATIBILITY
for faster, easier and safer hook-ups.



REVERSIBLE/REPLACEABLE HIGH-CARBON CUTTING EDGE

STANDARD AND
MEDIUM DUTY

REAR BLADES

FEATURES

Formed, curved moldboards for exceptional rigidity and strength (Standard Duty models)

360-degree pivoting blade with forward/reverse positions

Convenient parking stand standard

Five forward and five backfill angles, plus six offset positions (Medium Duty models)



Yanmar Rear Blades Specifications

GRADING & LEVELING

STANDARD DUTY

MODEL	YRB54S	YRB60S	YRB72S
Tractor Engine HP Range	up to 30 hp	up to 30 hp	
Tractor Hitch	Limited Cat 1 and 1		
Working Width (in.)	54	60	72
Approximate Weight (lbs)	144	151	162
Moldboard Height (in.)	12		
Moldboard Thickness (in.)	3/16 (grade 80 steel)		
Reversible Cutting Edge	3/8" x 6"		
Pivot Angle	Forward - 5 @ 15 degrees, Reverse - 5 @ 15 degrees		
Skid Shoes	Optional		
ASABE Quick Hitch Compatible	Yes		
Parking Stand	Optional		

STANDARD DUTY (PREMIUM)

MODEL	YRB60C	YRB72C	YRB84C
Tractor Engine HP Range	20-45 hp		
Tractor Hitch	Cat 1		
Working Width (in.)	60	72	84
Approximate Weight (lbs)	268	288	308
Moldboard Height (in.)	15		
Moldboard Thickness (in.)	1/4 (grade 80 steel)		
Reversible Cutting Edge	1/2" x 6"		
Pivot Angle	Forward - 5 @ 15 degrees, Reverse - 5 @ 15 degrees		
Tilt	up to 15 degrees		
Offset	up to 12" left or right		
End Plates	Optional		
Skid Shoes	Optional		
ASABE Quick Hitch Compatible	Yes		
Parking Stand	Optional		

MEDIUM DUTY*

MODEL	YRB720	YRB840	YRB960
Tractor Engine HP Range	30-75		
Tractor Hitch	Cat 1 & 2		
Moldboard Length (in.)	72	83	95
Moldboard Height (in.)	18		
Moldboard Thickness (in.)	0.313		
Approximate Weight (lbs.)	530	565	600
Angle Forward	360 degrees, 5 forward		
Angle Reverse	360 degrees, 5 reverse		
Tilt	5-position, up to 30 degrees		
Offset (in.)	4, 10 or 16 left or right		
End Plates	Optional		
Skid Shoes	Optional		

MEDIUM DUTY**

MODEL	YRB710	YRB830	YRB950	YRB830P	YRB950P
Tractor PTO HP	30-65 hp			40-8	
Tractor Hitch	Cat 1 & 2				
Working Width	71"	83"	95"	83"	95"
Moldboard Height	17"			17.5"	
Moldboard Thickness	0.250" (GR80)			0.313" (GR50)	
Reversible Cutting Edge Dimensions	0.5" x 6" double beveled				
Weight	455 lbs.	475 lbs.	495 lbs.	705 lbs.	730 lbs.
Pivot Angle	forward/reverse 7 @ 45°			up to 45° (mech or hyd)	
Offset	7 positions up to 18" (slides)			up to 18" (mech or hyd)	
Tilt	5 positions up to 23°			up to 23° (mech or hyd)	
End Plates	optional				
Skid Shoes	optional				
Tailwheel	-			optional	
ASABE Quick-Hitch Compatible	yes				
Parking Stand	standard				

*Available until December 2016

** Available December 2016